



www.vcx.com.pl

KARTA KATALOGOWA

BiWts – wkładki topikowe instalacyjne szybkie gF



Wkładki o charakterystyce gF

nr kat	nazwa	charakterystyka	prąd In	opakowanie szt.
BiWts E27/DII 4A	Wkładka topikowa instalacyjna szybka E27/DII 4A	gF/gL	4A	10
BiWts E27/DII 6A	Wkładka topikowa instalacyjna szybka E27/DII 6A	gF/gL	6A	10
BiWts E27/DII 10A	Wkładka topikowa instalacyjna szybka E27/DII 10A	gF/gL	10A	10
BiWts E27/DII 16A	Wkładka topikowa instalacyjna szybka E27/DII 16A	gF/gL	16A	10
BiWts E27/DII 20A	Wkładka topikowa instalacyjna szybka E27/DII 20A	gF/gL	20A	10
BiWts E27/DII 25A	Wkładka topikowa instalacyjna szybka E27/DII 25A	gF/gL	25A	10
BiWts E33/DIII 35A	Wkładka topikowa instalacyjna szybka E33/DIII 35A	gF/gL	35A	20
BiWts E33/DIII 50A	Wkładka topikowa instalacyjna szybka E33/DIII 50A	gF/gL	50A	20
BiWts E33/DIII 63A	Wkładka topikowa instalacyjna szybka E33/DIII 63A	gF/gL	63A	20

Informacje dotyczące bezpieczeństwa:

- Instalacja, konserwacja i ewentualna wymiana tego urządzenia musi być wykonywana wyłącznie przez wykwalifikowaną i uprawnioną osobę.
- Należy zastosować się do wszystkich odnośnych lokalnych, regionalnych i krajowych regulacji podczas instalacji, używania, konserwacji oraz wymiany urządzenia.
- Otwarcie lub jakakolwiek inna ingerencja w urządzenie powoduje utratę gwarancji.
- Obciążenia przekraczające wartości podane od Producenta mogą spowodować uszkodzenie samego urządzenia, jak i podłączonych układów elektrycznych.
- Eksploatacja i montaż urządzenia jest dozwolona wyłącznie z uwzględnieniem warunków zawartych w instrukcji i innych dokumentach dotyczących produktu.
- Przed przystąpieniem do pracy należy odłączyć zasilanie urządzenia.



www.vcx.com.pl

DATA SHEET

BiWts – fast-acting installation fuse links, gF



Fuse links with gF characteristics

Cat. No	name	characteristics	rated current In	package (pcs)
BiWts E27/DII 4A	Fast-acting installation fuse link E27/DII 4A	gF/gL	4A	10
BiWts E27/DII 6A	Fast-acting installation fuse link E27/DII 6A	gF/gL	6A	10
BiWts E27/DII 10A	Fast-acting installation fuse link E27/DII 10A	gF/gL	10A	10
BiWts E27/DII 16A	Fast-acting installation fuse link E27/DII 16A	gF/gL	16A	10
BiWts E27/DII 20A	Fast-acting installation fuse link E27/DII 20A	gF/gL	20A	10
BiWts E27/DII 25A	Fast-acting installation fuse link E27/DII 25A	gF/gL	25A	10
BiWts E33/DIII 35A	Fast-acting installation fuse link E33/DIII 35A	gF/gL	35A	20
BiWts E33/DIII 50A	Fast-acting installation fuse link E33/DIII 50A	gF/gL	50A	20
BiWts E33/DIII 63A	Fast-acting installation fuse link E33/DIII 63A	gF/gL	63A	20

Safety information:

- Installation, maintenance and possible replacement of this appliance must only be carried out by a qualified and authorised person.
- All relevant local, regional and national regulations must be complied with when installing, using, maintaining and replacing the unit.
- Opening or otherwise tampering with the unit will void the warranty.
- Loads exceeding the values specified from the manufacturer may damage the device itself as well as the connected electrical systems.
- Operation and assembly of the device is only permitted in accordance with the conditions contained in the manual and other product documents.
- Disconnect the power supply to the appliance before starting work.